

Dominique MARIAULLE et al.

internal resistance thereof, an RLC circuit close to the resonance is formed.--


REMARKS

Attached hereto is a marked-up version of the changes made to the Abstract and claims by the current amendment. The attached pages are captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE".

Respectfully submitted,

YOUNG & THOMPSON

By

  
Thomas W. Perkins  
Attorney for Applicants  
Registration No. 33,027  
745 South 23rd Street  
Arlington, VA 22202  
Telephone: 703/521-2297

January 3, 2002

10019527.040202

MARKED-UP VERSION OF CHANGES MADE TO THE CLAIMS

3. Device according to ~~one of Claims 1 or 2~~ claim 1, characterized in that the supply means (1) are connected to the work circuit via a voltage transformer ( $T_1$ ).

4. Device according to ~~one of the preceding Claims~~ claim 1, characterized in that the inductance ( $L_s$ ) arranged between the output terminals ( $S_1, S_2$ ) of the work circuit is such that, with the intrinsic capacitance of the handpiece (5) and the internal resistance thereof, an RLC circuit close to the resonance is formed.--

10019527.040202

MARKED-UP VERSION OF CHANGES MADE TO ABSTRACT

ABSTRACT OF THE DISCLOSURE

~~The invention relates to a~~ A power assistance device  
for an ultrasonic dental handpiece (5). ~~Said device comprises~~  
includes a working circuit ~~comprising with~~ a parallel imped-  
ance (Ls) between the output terminals (S1,S2) and a control  
circuit ~~which consists of~~ with a current transformer (T2),  
~~whereby~~ the primary winding (7) thereof is serially arranged  
in the working circuit and the secondary winding (11) thereof  
forms an RLC circuit in conjunction with a capacitor (13) and  
a resistor (15) associated therewith. ~~whereby the~~ The voltage  
of ~~said the~~ circuit at the terminals of the resistor (15) is  
transmitted to the input of ~~the above mentioned~~ a power supply  
(1). The control circuit ~~comprises means enabling~~ enables  
variations in the value of the capacitor (13) and/or the value  
of the self-inductance coil of the secondary winding (11) of  
the transformer (T2).

10019527.040202